



PIN	SYMBOL	DESCRIPTION
1	NC	
2	VSS	
3	NC	
4	NC	
5	NC	
6	NC	
7	NC	
8	NC	
9	NC	
10	NC	
11	VDD	
12	BS1	
13	BS2	
14	NC	
15	CS#	
16	RES#	
17	D/C#	
18	R/W#	
19	R/D#	
20	DO	
21	D1	
22	D2	
23	D3	
24	D4	
25	D5	
26	D6	
27	D7	
28	IREF	
29	VCOMH	
30	VCC	
31	NC	

NOTES:

- COLOR: YELLOW
- OPERATING VOLTAGE: VDD=3.0V (TYP.)
- DRIVE DUTY: 1/64
- DRIVER IC: SPD0301
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 6800/8080 PARALLEL, 4-WIRE SPI, I²C
- GENERAL TOLERANCE: ±0.5MM
- ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	RITA	2021.09.15	MODULE P/N:
CHECKED BY:			MI12864AG0-Y2
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		OLED MODULE
UNIT:	mm		
SHEET NO.:	1/1		

01	FIRST ISSUE	RITA	2021.09.15
VER.	REVISED DESCRIPTION	REVISER	DATE