



Pin	Symbol
1	N.C. (GND)
2	VSS
3	VCC
4	VCOMH
5	VLSS
6	D7
7	D6
8	D5
9	D4
10	D3
11	D2
12	D1
13	DO
14	E/RD#
15	R/W#
16	BS0
17	BS1
18	D/C#
19	CS#
20	RES#
21	FE
22	REF
23	N.C.
24	VDDIO
25	VDD
26	VCI
27	VSL
28	VLSS
29	VCC
30	N.C. (GND)

- Notes:
1. Color: White
  2. Driver IC: SSD1322
  3. Interface:  
8-bit 68XX/80XX Parallel, 3-/4-wire SPI
  4. General Tolerance: ±0.30
  5. The total thickness (2.10 Max) is without polarizer protective film & remove tape.  
The actual assembled total thickness with above materials should be 2.35 Max.

**MULTI-INNO TECHNOLOGY CO., LTD.**

DRAWN BY:	RITA	2017.11.03	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	M112864HO-W
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			OLED MODULE

VER.	FIRST ISSUE	REVISER	DATE
01		RITA	2017.11.03
	REVISED DESCRIPTION		