



Pin	Symbol
1	N.C. (GND)
2	VSS
3	VCC
4	VCOMH
5	VLSS
6	D7
7	D6
8	D5
9	D4
10	D3
11	D2
12	D1
13	D0
14	E/RD+
15	R/W
16	BS0
17	BS1
18	D/C+
19	CS+
20	RES+
21	FR
22	REF
23	N.C.
24	VDDIO
25	VDD
26	VCI
27	VSL
28	VLSS
29	VCC
30	N.C.(GND)

- Notes:
1. Color: Yellow
 2. Driver IC: SSD1322
 3. Interface:
8-bit 68XX/80XX Parallel, 3-/4-wire SPI
 4. General Tolerance: ±0.30
 5. The total thickness (2.10 Max) is without polarizer protective film & remove tape.
The actual assembled total thickness with above materials should be 2.35 Max.

MIT MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	RITA	2017.10.30	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT: mm	MI12864AHO-Y
APPROVED BY:				DESCRIPTION:
VERSION NO:	01			OLED MODULE

VER.	FIRST ISSUE	REVISER	DATE
01	FIRST ISSUE	RITA	2017.10.30