



Detail "A"
Scale (10:1)

PIN DESCRIPTION	
PIN	SYMBOL
1	N.C.(GND)
2	C2P
3	C2N
4	C1P
5	C1N
6	VBAT
7	N.C.
8	VSS
9	VDD
10	BS0
11	BS1
12	NC
13	CS#
14	RES#
15	D/C#
16	N.C.
17	N.C.
18	D0
19	D1
20	D2
21	N.C.
22	N.C.
23	N.C.
24	N.C.
25	N.C.
26	IREF
27	VCOMH
28	VCC
29	VLSS
30	N.C.(GND)

NOTES:

- COLOR: WHITE
- DRIVE DUTY: 1/64
- DRIVER IC: SSD1315
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 3-/4-WIRE SPI, I²C
- ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL	2019.05.23	MODULE P/N:
CHECKED BY:			MI12864AIO-W
APPROVED BY:			SCALE : 1/1
VERSION NO:	01		UNIT: mm
			DESCRIPTION:
			SHEET NO.: 1/1
			OLED MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
01	FIRST ISSUE	CAROL	2019.05.23