



PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	VCC
3	VCOMH
4	IREF
5	D7
6	D6
7	D5
8	D4
9	D3
10	D2
11	D1
12	D0
13	E(RD#)
14	R/W(WR#)
15	D/C#
16	RES#
17	CS#
18	NC
19	BS2
20	BS1
21	VDD
22	NC
23	NC
24	NC
25	NC
26	NC
27	NC
28	NC
29	VSS
30	VSL

- NOTES:
- COLOR: YELLOW
 - OPERATING VOLTAGE: VCC=15V (TYP.)
 - DRIVE DUTY: 1/64
 - DRIVER IC: SPD0301
 - OPERATING TEMP.: -40°C ~ 70°C
 - STORAGE TEMP.: -40°C ~ 85°C
 - INTERFACE: 8-BIT 6800/8080 PARALLEL, 4-WIRE SPI, IIC
 - ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
 - GENERAL TOLERANCE: ±0.5MM
 - ROHS COMPLIANT

Mit MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL 2021.10.26		MODULE P/N:
CHECKED BY:		SCALE : 1/1	M12864AL0-Y
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO:	01	SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	CAROL	2021.10.26
VER.	REVISED DESCRIPTION	REVISER	DATE