



PIN DESCRIPTION	
PIN	SYMBOL
1	VSS
2	VCC
3	VDD
4	BS0
5	BS1
6	BS2
7	CS#
8	RES#
9	D/C#
10	W/R#
11	R/D
12	D0
13	D1
14	D2
15	D3
16	D4
17	D5
18	D6
19	D7
20	IREF
21	VCOMH
22	VCC
23	VSS
24	NC

NOTES:

- COLOR: WHITE
- DRIVE DUTY: 1/64
- DRIVER IC: CH1116
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 6800/8080 PARALLEL, 3-/4-WIRE SPI, IIC
- ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
- GENERAL TOLERANCE: ±0.5MM
- ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL	2022.08.19	MODULE P/N:
CHECKED BY:			MI12864AM0-W
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		OLED MODULE
		SCALE : 1/1	UNIT: mm
		SHEET NO.: 1/1	

01	FIRST ISSUE	CAROL	2022.08.19
VER.	REVISED DESCRIPTION	REVISER	DATE