



PIN ASSIGNMENT	
PIN	SYMBOL
1	NC
2	V0
3	V1
4	V2
5	V3
6	V4
7	C2-
8	C2+
9	C1+
10	C1-
11	C3+
12	Vout
13	VSS
14	VDD
15	SI
16	SCL
17	RS
18	/RST
19	/CS1
20	NC
21	K
22	K
23	A
24	A

- NOTES:
1. DISPLAY TYPE: FSTN, TRANSFLECTIVE, POSITIVE.
  2. DRIVE METHOD: 1/65DUTY, 1/9BIAS, VDD=3.0V, VOP=9.0V.
  3. VIEWING DIRECTION: 12 O'CLOCK.
  4. IC DRIVER: ST7565R OR EQUIVALENT.
  5. OPERATING TEMP.: -20~70°.
  6. STORAGE TEMP.: -30~80°.
  7. LED BACKLIGHT: WHITE, EDGE, LEDA-LEDK=3.3V.
  8. GENERAL TOLERANCE: ±0.2mm.
  9. ROHS COMPLIANT.

DOTS DETAIL SCALE:10:1

**MIT** MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	20120719	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI12864AP-G-1
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			GRAPHIC MODULE

01	FIRST ISSUE	CAROL	2012.07.19
VER.	REVISED DESCRIPTION	REVISER	DATE