



Detail "A"

| PIN ASSIGNMENT | |
|----------------|--------|
| NO. | SYMBOL |
| 1 | VSS |
| 2 | VDD |
| 3 | VO |
| 4 | RS |
| 5 | RW |
| 6 | E |
| 7 | DB0 |
| 8 | DB1 |
| 9 | DB2 |
| 10 | DB3 |
| 11 | DB4 |
| 12 | DB5 |
| 13 | DB6 |
| 14 | DB7 |
| 15 | CS1 |
| 16 | CS2 |
| 17 | RST |
| 18 | VEE |
| 19 | LEDA |
| 20 | LEDK |

NOTES:

1. DISPLAY TYPE: STN (BLUE), TRANSMISSIVE, NEGATIVE \triangle
2. DRIVE METHOD: 1/64 DUTY, 1/9 BIAS, VDD=5.0V, VOP=10.5V
3. VIEWING DIRECTION: 6:00 O'CLOCK
4. IC DRIVER: AIP31107 + AIP31108
5. OPERATING TEMP.: -20°C ~ 70°C
6. STORAGE TEMP.: -30°C ~ 80°C
7. BACKLIGHT: WHITE LED
8. GENERAL TOLERANCE: $\pm 0.3\text{MM}$
9. ROHS COMPLIANT

| | | | |
|--|------|----------|--------------------------------|
| MULTI-INNO TECHNOLOGY CO., LTD. | | | |
| DRAWN BY: | RITA | 20170216 | SCALE : 1/1 |
| CHECKED BY: | | | UNIT: mm |
| APPROVED BY: | | | DESCRIPTION: GRAPHIC MODULE |
| VERSION NO: | 02 | | |

| VER. | REVISED DESCRIPTION | REVISER | DATE |
|------|-----------------------------------|---------|------------|
| 02 | CORRECT THE DISPLAY TYPE IN NOTES | RITA | 2019.05.29 |
| 01 | FIRST ISSUE | RITA | 2017.02.16 |