



DETAIL A  
(SCALE 10:1)

FUNCTION TABLE

	SEG127	SEGO	
COM0			COM0
COM32			COM31
COM63			

PIN DESCRIPTION	
PIN	SYMBOL
1	/CS1
2	/REST
3	A0
4	/WR
5	/RD
6	D0
7	D1
8	D2
9	D3
10	D4
11	D5
12	D6
13	D7
14	VDD
15	VSS
16	VOUT
17	C3+
18	C1-
19	C1+
20	C2+
21	C2-
22	V4
23	V3
24	V2
25	V1
26	V0
27	VR
28	C86
29	P/S
30	NC

NOTES:

1. DISPLAY TYPE: FSTN, TRANSFLETIVE, POSITIVE
2. OPERATING VOLTAGE: VDD=3.3V, VOP=9.2V
3. DRIVE METHOD: 1/65DUTY, 1/9BIAS
4. VIEWING DIRECTION: 6 O'CLOCK
5. DRIVER IC: ST7565P
6. OPERATING TEMP.: -20°C ~ 70°C
7. STORAGE TEMP.: -30°C ~ 80°C
8. LED BACKLIGHT: -
9. ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
10. GENERAL TOLERANCE: ±0.3MM
11. ROHS COMPLIANT

01	FIRST ISSUE	CAROL	2022.10.11	APPROVED BY:		UNIT: mm	DESCRIPTION:
VER.	REVISED DESCRIPTION	REVISER	DATE	VERSION NO:	01	SHEET NO.: 1/1	GRAPHIC MODULE

**MIT** MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2022.10.11		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI12864CD-G