


Pin Assignment	
NO.	SYMBOL
1	NC(GND)
2	VLSS
3	VSS
4	NC
5	VDD
6	BS1
7	BS2
8	CS#
9	RES#
10	D/C#
11	R/W#
12	E/RD#
13	D0
14	D1
15	D2
16	D3
17	D4
18	D5
19	D6
20	D7
21	IREF
22	VCOMH
23	VCC
24	NC(GND)



- NOTES:
1. DISPLAY TYPE: PASSIVE MATRIX, MONOCHROME (WHITE).
 2. DUTY: 1/64.
 3. OPERATING VOLTAGE: VDD=1.65~3.3V, VCC=12.5V.
 4. DRIVER IC: SPD0301.
 5. OPERATING TEMP.: -40°C ~ 70°C.
 6. STORAGE TEMP.: -40°C ~ 85°C.
 7. INTERFACE: 8-BIT 8080 PARALLEL MPU.
 8. GENERAL TOLERANCE: ±0.3MM.
 9. ROHS COMPLIANT.

MIT MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2020.05.11		MODULE P/N:
CHECKED BY:		SCALE : 1/1	MI12864CBO-W
APPROVED BY:		UNIT: mm	DESCRIPTION:
VER.	01	SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	CAROL	2020.05.11
VER.	REVISED DESCRIPTION	REVISER	DATE