



PIN DESCRIPTION	
PIN	SYMBOL
1	NC (GND)
2	VLSS
3	VSS
4	NC (GND)
5	VDD
6	BS1
7	BS2
8	CS#
9	RES#
10	D/C#
11	R/W#
12	E/RD#
13	D0
14	D1
15	D2
16	D3
17	D4
18	D5
19	D6
20	D7
21	IREF
22	VCOMH
23	VCC
24	NC (GND)

- NOTES:
- COLOR: WHITE
 - OPERATING VOLTAGE: VDD=2.8V (TYP.)
 - DRIVE DUTY: 1/64
 - DRIVER IC: SSD1309
 - OPERATING TEMP.: -40°C ~ 70°C
 - STORAGE TEMP.: -40°C ~ 85°C
 - INTERFACE: 8-BIT 6800/8080 PARALLEL, 4-WIRE SPI, I²C
 - GENERAL TOLERANCE: ±0.3MM
 - ROHS COMPLIANT

MiI MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2023.01.10		MODULE P/N:			
CHECKED BY:			SCALE : 1/1	M12864GCO-W			
APPROVED BY:			UNIT: mm	DESCRIPTION:			
VER.	REVISED DESCRIPTION	REVISER	DATE	VERSION NO:	01	SHEET NO.: 1/1	OLED MODULE