


PIN	SYMBOL
1	A
2	K
3	V0
4	V1
5	V2
6	V3
7	V4
8	CAP2-
9	CAP2+
10	CAP1+
11	CAP1-
12	CAP3+
13	VOUT
14	VSS
15	VDD
16	D7<SDA>
17	D6<SCL>
18	A0
19	/RES
20	/CS1


NOTES:

1. DISPLAY TYPE: FSTN
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSLLECTIVE/POSITIVE
4. LCD CONTROLLER: ST7565P
5. DRIVE METHOD: 1/65 DUTY BIAS: 1/9
6. VDD: 3.0V
7. OPERATING VOLTAGE: 10V
8. BACKLIGHT: Y/G LED-8CHIP,VBL=3.0V,IF=120mA
9. OPERATING TEMP: -30°C~70°C
10. STORAGE TEMP: -30°C~80°C
11. UNMARKED TOLERANCE:±0.3
12.   MEANS IMPORTANT DIMENSION
13. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS



DETAIL A  
20:1

CIRCUIT DIAGRAM



CUSTOMER APVL		CUSTOMER		DATE	
DRAWN		SCALE		TITLE	
DFTG CHK		UNIT		MI12864H1-G	
ENGR CHK		mm			
APPROVAL				MODEL	
MULTI-INNO TECHNOLOGY CO.,LTD.				DWG NO	
				PAGE 1/1	