



PIN	SYMBOL
1	A
2	K
3	V0
4	V1
5	V2
6	V3
7	V4
8	CAP2-
9	CAP2+
10	CAP1+
11	CAP1-
12	CAP3+
13	VOUT
14	VSS
15	VDD
16	D7<SDA>
17	D6<SCL>
18	A0
19	/RES
20	/CS1



NOTES:

1. DISPLAY TYPE: FSTN, TRANSFLECTIVE, POSITIVE.
2. DRIVE METHOD: 1/65DUTY, 1/9BIAS, VDD=3.0V, VOP=10.0V.
3. IC DRIVER: ST7565P-G.
4. OPERATING TEMP.: -30°~70°.
5. STORAGE TEMP.: -30°~80°.
6. BACKLIGHT TYPE.: 8-CHIP WHITE LED, IF=120mA, VF=3.6V.
7. GENERAL TOLERANCE: ±0.3mm.
8. ROHS COMPLIANT.

 <b>MULTI-INNO TECHNOLOGY CO.,LTD.</b>			
DRAWN BY:	RITA	2017.12.07	SCALE : 1/1
CHECKED BY:			UNIT: mm
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		MODULE P/N: MI12864H1-G-1
			GRAPHIC MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
01	FIRST ISSUE	RITA	2017.12.07