



PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	NC
3	NC
4	NC
5	NC
6	VG
7	NC
8	NC
9	XYO
10	VO
11	NC
12	NC
13	VSS
14	VDD
15	SDA
16	SCLK
17	A0
18	RSTB
19	CSB
20	NC

- NOTES:
1. DISPLAY TYPE: FSTN, TRANSFLECTIVE, POSITIVE.
  2. DRIVE METHOD: 1/65DUTY, 1/9BIAS, VDD=3.0V, VOP=8.7V.
  3. VIEWING DIRECTION: 6:00 O'CLOCK.
  4. IC DRIVER: ST7567.
  5. OPERATING TEMP.: -20°~70°.
  6. STORAGE TEMP.: -30°~80°.
  7. BACKLIGHT TYPE.: 4-CHIP WHITE LED, IF=60mA, VF=4.0V(TYPE).
  8. GENERAL TOLERANCE: ±0.3mm.
  9. ROHS COMPLIANT.

MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY:	CAROL	2010.05.08	MODULE P/N:
CHECKED BY:			MI12864J-G-8
APPROVED BY:			UNIT: mm
VERSION NO:	01		SHEET NO: 1/1
VER.	REVISED DESCRIPTION	REVISOR	DATE
01	FIRST ISSUE	CAROL	2010.05.08
			DESCRIPTION:
			GRAPHIC MODULE