



PIN	SYMBOL
1	NC
2	NC
3	NC
4	NC
5	NC
6	VG
7	NC
8	NC
9	XV0
10	V0
11	NC
12	NC
13	VSS
14	VDD
15	SDA
16	SCLK
17	AO
18	RSTB
19	CSB
20	NC

1. DISPLAY TYPE: STN BLUE
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSMISSIVE/ NEGATIVE
4. OPERATING TEMP: -20° --- +70° C
5. STORAGE TEMP: -30° --- +80° C
6. LCD OPERATING VOLTAGE: \triangle 8.7V VDD=3.0V
7. DRIVE METHOD: 1/65 DUTY 1/9BIAS
8. CONTROLLER: ST7567
9. BACKLIGHT: LED(White; 4 DIES) V=4V(TYPE) I=60mA
10. CONNECTOR: FPC
11. UNMARKED TOLERANCES: ± 0.3 mm
12. THE CONTROLLED DIMENSION MASK TO BE
13. REQUIREMENT ON ENVIRONMENTAL PROTECTION: RoHS

CUSTOMER APVL	CUSTOMER	DATE	TITLE
DRAWN	SCALE	UNIT	M112864J-G-8A
DFTG CHK	mm		
ENGR CHK	MODEL		
APPROVAL		DWG NO	PAGE 1/1
MULTI-INNO TECHNOLOGY CO.,LTD.			