



Pin	Symbol
1	N.C. (GND)
2	C2P
3	C2N
4	C1P
5	C1N
6	VBAT
7	N.C.
8	VSS
9	VDD
10	BS0
11	BS1
12	BS2
13	CS#
14	RES#
15	D/C#
16	R/W#
17	E/RD#
18	D0
19	D1
20	D2
21	D3
22	D4
23	D5
24	D6
25	D7
26	IREF
27	VCOMH
28	VCC
29	VLSS
30	N.C. (GND)

Notes:

1. Color: Light Blue
2. Driver IC: SSD1306
3. Interface:
8-bit 68XX/80XX Parallel, 3-/4-wire SPI, I2C
4. General Tolerance: ±0.30
5. The total thickness (1.55 Max) is without polarizer protective film & remove tape.
The actual assembled total thickness with above materials should be 1.80 Max.

MIT MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2016.03.22	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI12864L10-B
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	02			OLED MODULE

VER.	DESCRIPTION	REVISER	DATE
02	MODIFY THE THICKNESS OF THE MODULE	RITA	2018.01.12
01	FIRST ISSUE	RITA	2016.03.22
	REVISED DESCRIPTION		