


COM&SEG LAYOUT



Dots Detail  
SCALE 10X

PIN	SYMBOL	PIN DESCRIPTION
1	NC(GND)	
2	VSS	
3	NC	
4	NC	
5	NC	
6	NC	
7	NC	
8	NC	
9	NC	
10	NC	
11	VDD	
12	BS1	
13	BS2	
14	NC	
15	CS#	
16	RES#	
17	DC#	
18	R/W#	
19	E/RD#	
20	D0	
21	D1	
22	D2	
23	D3	
24	D4	
25	D5	
26	D6	
27	D7	
28	IREF	
29	VCOMH	
30	VCC	
31	NC(GND)	

NOTES:

- COLOR: WHITE
- DRIVE DUTY: 1/64
- DRIVER IC: SSD1309
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 6800/8080 PARALLEL, 4-WIRE SPI, I<sup>2</sup>C
- ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT



MULTI-INNO TECHNOLOGY CO., LTD.

01	FIRST ISSUE	CAROL	2022.10.24	APPROVED BY:	SCALE : 1/1	MODULE P/N:
VER.	REVISED DESCRIPTION	REVISER	DATE	VERSION NO:	UNIT: mm	MI12864M20-W
				01	SHEET NO.: 1/1	DESCRIPTION:
						OLED MODULE