



FPC PIN DESCRIPTION

| | |
|----|-------|
| 1 | VPP |
| 2 | VCOMH |
| 3 | IREF |
| 4 | D7 |
| 5 | D6 |
| 6 | D5 |
| 7 | D4 |
| 8 | D3 |
| 9 | D2 |
| 10 | D1 |
| 11 | D0 |
| 12 | RDB |
| 13 | WRB |
| 14 | A0 |
| 15 | RESB |
| 16 | CSB |
| 17 | P/S |
| 18 | C86 |
| 19 | VDD |
| 20 | NC |
| 21 | NC |
| 22 | NC |
| 23 | NC |
| 24 | VSS |

NOTES:

1. OPERATING TEMPERATURE: -20°C TO 70°C
2. STORAGE TEMPERATURE: -30°C TO 80°C
3. DRIVER IC: SSD1308Z
4. GENERAL TOLERANCE: ±0.2
5. ROHS COMPLIANCY

| | | | |
|--------------------------------|----------|-------------|------|
| CUSTOMER APVL | CUSTOMER | DATE | |
| DRAWN | SCALE | TITLE | |
| DFTG CHK | UNIT | MI12864R0-Y | |
| ENGR CHK | mm | MODEL | |
| APPROVAL | | | |
| MULTI-INNO TECHNOLOGY CO.,LTD. | | DWG NO | PAGE |
| | | | 1/1 |