



NOTES:

- COLOR: WHITE
- OPERATING VOLTAGE: VDD=3.0V (TYP.)
- DRIVE DUTY: 1/64
- DRIVER IC: CH1116
- OPERATING TEMP.: -40°C ~ 85°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 68XX/80XX PARALLEL, 3-/4-WIRE SPI, I²C
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT

PIN	SYMBOL	PIN DESCRIPTION
1	N.C.(GND)	
2	C2P	
3	C2N	
4	C1P	
5	C1N	
6	VBAT	
7	VSS	
8	VSS	
9	VDD	
10	BS0	
11	BS1	
12	BS2	
13	CS#	
14	RES#	
15	D/C#	
16	R/W#	
17	E/RD#	
18	D0	
19	D1	
20	D2	
21	D3	
22	D4	
23	D5	
24	D6	
25	D7	
26	IREF	
27	VCOMH	
28	VCC	
29	NC	
30	N.C.(GND)	

		MULTI-INNO TECHNOLOGY CO., LTD.	
		DRAWN BY: CAROL 2020.06.15	
CHECKED BY:	SCALE : 1/1	DESCRIPTION:	
APPROVED BY:	UNIT: mm	SHEET NO.: 1/1	
VERSION NO: 01	REVISER: CAROL 2020.06.15	DATE: 2020.06.15	DESCRIPTION: OLED MODULE

01	FIRST ISSUE	CAROL	2020.06.15
VER.	REVISED DESCRIPTION	REVISER	DATE