



Detail "A"
Scale 20:1

PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	VSDH
3	VDDH
4	VSSH
5	IREF
6	OSCA2
7	OSCA1
8	VDDIO
9	VSYNCO
10	VSYN
11	HSYN
12	DOTCLK
13	ENABLE
14	CPU
15	PS
16	D17
17	D16
18	D15
19	D14
20	D13
21	D12
22	D11
23	D10
24	D9
25	RS
26	CSB
27	RDB
28	WRB
29	RESETB
30	VSS
31	VDD
32	VSSH
33	VDDH
34	VSDH
35	NC

- NOTES:
1. DISPLAY TYPE: PASSIVE MATRIX OLED, 262,141 COLORS.
 2. DUTY: 1/128.
 3. OPERATING VOLTAGE: VDD=2.8V, VDDH=14V.
 4. DRIVER IC: SEPS525.
 5. OPERATING TEMP.: -40°C ~ 70°C. \triangle
 6. STORAGE TEMP.: -40°C ~ 80°C.
 7. INTERFACE: 8-/9-BIT CPU, 6-BIT RGB, 4-WIRE SPI.
 8. GENERAL TOLERANCE: ±0.3mm.
 9. RoHS COMPLIANT.

VER.	REVISED DESCRIPTION	REVISER	DATE
02	CORRECT OPERATING TEMP. FROM -30°C TO -40°C.	CAROL	2012.12.26
01	FIRST ISSUE	LEON	2006.08.01

MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	LEON	2006.08.01		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI160128A0
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	02		SHEET NO.: 1/1	OLED MODULE