


PIXEL DETAIL
(SCALE 20:1)



SEG & COM LAYOUT

PIN ASSIGNMENT	
PIN	SYMBOL
1	NC(GND)
2	VCC
3	NC
4	NC
5	BS1
6	BS2
7	VSS
8	IREF
9	CS#
10	RES#
11	D/C#
12	R/W#
13	E/RD#
14	D0
15	D1
16	D2
17	D3
18	D4
19	D5
20	D6
21	D7
22	VDD
23	VCOMH
24	VCC

NOTES:

- COLOR: WHITE
- OPERATING VOLTAGE: VDD=2.85V (TYP.), VCC=14V (TYP.)
- DRIVE DUTY: 1/160
- DRIVER IC: SSD1320
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 6800/8080 PARALLEL, 4-WIRE SPI, IIC
- SURFACE LUMINANCE: 100CD/M² (TYP.)
- LIFETIME: 40,000 HOURS (TYP.)
- RECOMMEND MATCHING CONNECTOR: I-PEX 20542-024E-01 DOUBLE-SIDED CONTACT OR EQUIVALENT
- UNMARKED TOLERANCE: ±0.3MM
- ROHS COMPLIANT

MULTI-INNO TECHNOLOGY CO., LTD.			MODULE P/N:
		DRAWN BY: RITA CHECKED BY: APPROVED BY: VERSION NO: 01	SCALE : 1/1 UNIT: mm SHEET NO: 1/1

01	FIRST ISSUE	RITA	2025.08.20
VER.	REVISED DESCRIPTION	REVISER	DATE