

DISPLAY PATTERN


PIN ASSIGNMENT	
PIN NO	SYMBOL
1	XRESET
2	RS
3	CSB
4	SCL
5	SI
6	VSS
7	VDD
8	VOUT
9	CAP1P
10	CAP1N

NOTES:

1. DISPLAY TYPE: FSTN, TRANSFLETIVE, POSITIVE
2. OPERATING VOLTAGE: VDD=3.3V, VOP=4.5V
3. DRIVE METHOD: 1/16DUTY, 1/5BIAS
4. VIEWING DIRECTION: 12:00 O'CLOCK
5. DRIVER IC: UC17032
6. OPERATING TEMP.: -10°C ~ 60°C
7. STORAGE TEMP.: -20°C ~ 70°C
8. BACKLIGHT: -
9. GENERAL TOLERANCE: ±0.2MM
10. ROHS COMPLIANT

01	FIRST ISSUE	RITA	2021.08.09	APPROVED BY:	UNIT: mm	DESCRIPTION:
VER.	REVISED DESCRIPTION	REVISER	DATE	VERSION NO:	01	CHARACTERS MODULE

 MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2021.08.09		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI1602A1F-G
SHEET NO.:	1/1			