


PIN DESCRIPTION

PIN NO	SYMBOL
1	XRESET
2	RS
3	CSB
4	SCL
5	SI
6	VSS
7	VDD
8	VOUT
9	CAP1P
10	CAP1N



DISPLAY PATTERN

NOTES:

1. DISPLAY TYPE: FSTN, TRANSFLECTIVE, POSITIVE.
2. OPERATING VOLTAGE: VDD=3.3V, VOP=4.5.
3. VIEWING DIRECTION: 12 O'CLOCK.
4. IC DRIVER: ST7032I-0D.
5. OPERATING TEMP: -10°C ~ 60°C.
6. STORAGE TEMP: -20°C ~ 70°C.
7. DRIVER METHOD: 1/16 DUTY, 1/5 BIAS.
8. INTERFACE: SPI.
9. GENERAL TOLERANCE: ±0.2.
10. RoHS COMPLIANT.



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2014.08.28	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI1602AF-G
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		CHARACTERS MODULE

01	FIRST ISSUE	2014.08.28
VER.	REVISED DESCRIPTION	DATE