



PIN DESCRIPTION	
PIN	SYMBOL
1	VSS
2	VDD
3	VO
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LEDA
16	LEDK

NOTES:

- LCD TYPE: STN, BLUE, NEGATIVE, TRANSMISSIVE.
- VIEWING DIRECTION: 6:00 O'CLOCK.
- DRIVE METHOD: 1/16 DUTY, 1/5BIAS.
- OPERATING VOLTAGE: VDD=5.0, VOP=4.7V.
- CONTROLLER: AIP31066 OR COMPATIBLE.
- OPERATING TEMP.: -20°C ~ 70°C.
- STORAGE TEMP.: -30°C ~ 80°C.
- BACKLIGHT: WHITE LED, IF=30mA, VF=3.1V.
- GENERAL TOLERANCE: ±0.2.
- ROHS COMPLIANT.

DETAIL "A"

 MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	CAROL 2015.03.12		MODULE P/N:
CHECKED BY:		SCALE : 1/1	MI1602AH
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO:	02	SHEET NO.: 1/1	CHARACTER MODULE

02	CORRECT DRAWING WRONG SIZE.	CAROL	2020.12.15
01	FIRST ISSUE	CAROL	2015.03.12
VER.	REVISED DESCRIPTION	REVISER	DATE