



PIN DESCRIPTION	
PIN	SYMBOL
1	VSS
2	VDD
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	NC
16	NC

NOTES:

1. DISPLAY TYPE: STN(GRAY), REFLECTIVE, POSITIVE
2. OPERATING VOLTAGE: VDD=5.0V, VOP=4.7V
3. DRIVE METHOD: 1/16DUTY, 1/5BIAS
4. VIEWING DIRECTION: 6 O'CLOCK
5. DRIVER IC: AIP31066
6. OPERATING TEMP.: -0°C ~ 50°C
7. STORAGE TEMP.: -20°C ~ 70°C
8. GENERAL TOLERANCE: ±0.3MM
9. ROHS COMPLIANT

01	FIRST ISSUE	CAROL	2020.08.23	APPROVED BY:		UNIT: mm	DESCRIPTION:
VER.	REVISED DESCRIPTION	REVISER	DATE	VERSION NO:	01	SHEET NO.: 1/1	CHARACTER MODULE


MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2020.08.23		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI1602AJ-2
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	CHARACTER MODULE