



NOTES:

- |   |  |
|---|--|
| 1. DISPLAY TYPE:  | FSTN   |
| 2. CHARACTERS:  | 16 X 2 LINES   |
| 3. VIEWING DIRECTION:   | 6:00   |
| 4. POLARIZER MODE:  | REFLECTIVE/POSITIVE  |
| 5. DRIVE METHOD:  | 1/16 DUTY 1/5 BIAS   |
| 6. LCD OPERATING VOLTAGE:   | 6.5V   |
| 7. VDD:   | 3.0V   |
| 8. OPERATING TEMP.:   | -20°C~+70°C  |
| 9. STORAGE TEMP.:   | -30°C~+90°C  |
| 10. CONNECTOR:  | FPC  |
| 11. CONTROLLER:   | ST7032-0D  |
| 12. UNMARKED TOLERANCES:  | $\pm 0.2\text{mm}$   |
| 13. THE CONTROLLED DIMENSION MASK TO BE                               | <span style="border: 1px solid black; display: inline-block; width: 20px; height: 10px;"></span> |
| 14. REQUIREMENT ON ENVIRONMENTAL PROTECTION:                          | RoHS   |
| 15. PERFORMANCE MAY NOT BE OPTIMIZED AT THE EXTREME TEMPERATURE RANGE |  |

PIN	1	2	3	4	5	6	7	8	9	10
SYMBOL	RES	RS	CSB	R/W	E	DB0	DB1	DB2	DB3	DB4
PIN	11	12	13	14	15	16	17	18	19	
SYMBOL	DB5	DB6	DB7	VSS	VDD	VOUT	PSB	PS12B	CLS	

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI1602D-G	
ENGR CHK	mm	MODEL	
APPROVAL		MODEL	
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE
			1/1