



PIN DESCRIPTION	
PIN	SYMBOL
1	COMG
2	SEGG
3	V16
4	VFS
5	VCC1
6	SHL
7	C68
8	PS
9	CMS
10	SCS
11	iIC
12	RESETB
13	DB7
14	DB6
15	DB5
16	DB4
17	DB3
18	DB2
19	DB1
20	DB0
21	R_WB
22	E
23	RS
24	CSB
25	VDD
26	GND
27	IERSEL
28	OSC2
29	OSC1
30	DVR
31	RESE
32	FB
33	BVR
34	GDR
35	VCC2
36	VSS2

NOTES:

- COLOR: WHITE
- OPERATING VOLTAGE: VCC1=3.3V (TYP.)
- DRIVE DUTY: 1/16
- DRIVER IC: RT1305CA1-B
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 4-/8-BIT 6800/8080 PARALLEL, 3-/4-WIRE SPI, I<sup>2</sup>C
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2022.01.24		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI1602HO-W
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	CAROL	2022.01.24
VER.	REVISED DESCRIPTION	REVISER	DATE