



PIN ASSIGNMENT	
NO.	SYMBOL
1	VSS
2	VDD
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LEDA
16	LEDK

NOTES:

1. DISPLAY TYPE: STN(GRAY),TRANSFLECTIVE,POSITIVE.
2. DRIVE METHOD: 1/16DUTY, 1/5BIAS, VDD=5.0V, VOP=4.7V.
3. IC DRIVER: AIP31066.
4. OPERATING TEMP.: -20~70°.
5. STORAGE TEMP.: -30~80°.
6. BACKLIGHT TYPE.: WHITE LED.
7. GENERAL TOLERANCE: ±0.2mm.
8. ROHS COMPLIANT.

MIT MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	RITA	2018.05.31	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI1604L
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			CHARACTER MODULE

01	FIRST ISSUE	RITA	2018.05.31
VER.	REVISED DESCRIPTION	REVISER	DATE