


PIN ASSIGNMENT	
PIN	SYMBOL
1	VSS
2	VDD
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LEDA
16	LEDK

NOTES:

1. DISPLAY TYPE: STN(Y-G), TRANSFLECTIVE, POSITIVE.
2. DRIVER METHOD: 1/6DUTY, 1/5BIAS, VOP=4.7V±0.3.
3. VIEWING DIRECTION: 6 O'CLOCK.
4. DRIVER IC: AIP31066 OR COMPATIBLE.
5. OPERATING TEMP.: -20°C ~ 70°C.
6. STORAGE TEMP.: -30°C ~ 80°C.
7. LED BACKLIGHT: YELLOW-GREEN LED.
8. GENERAL TOLERANCE: ±0.3MM.
9. ROHS COMPLIANT.

 MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY:	CAROL	2020.04.03	MODULE P/N:
CHECKED BY:			MI1604L-1
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		CHARACTER MODULE
		SCALE : 1/1	UNIT: mm
		SHEET NO.: 1/1	

01	FIRST ISSUE	CAROL	2020.04.03
VER.	REVISED DESCRIPTION	REVISOR	DATE