



PIN ASSIGNMENT	
PIN	SYMBOL
1	COMG
2	SEGG
3	V16
4	VFS
5	VCC1
6	SHL
7	C68
8	PS
9	CMS
10	SGS
11	IIC
12	RESETB
13	DB7
14	DB6
15	DB5
16	DB4
17	DB3
18	DB2
19	DB1
20	DB0
21	R_WB
22	E
23	RS
24	CSB
25	VDD
26	GND
27	IERSEL
28	OSC2
29	OSC1
30	DVR
31	BVR
32	NC
33	NC

NOTES:

- COLOR: WHITE
- OPERATING VOLTAGE: VCC1=2.85V (TYP.)
- DRIVE DUTY: 1/16
- DRIVER IC: RT1305CA1-B
- OPERATING TEMP: -40°C ~ 85°C
- STORAGE TEMP: -40°C ~ 90°C
- INTERFACE: 8080-/6800-SERIES 4-/8-BIT PARALLEL BI-DIRECTIONAL INTERFACE, 3-/4-WIRE SPI INTERFACE, IIC INTERFACE
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT

**Mit** MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL		MODULE P/N:
CHECKED BY:		SCALE : 1/1	M12002B0-W
APPROVED BY:		UNIT: mm	DESCRIPTION:
VERSION NO:	01	SHEET NO: 1/1	OLED MODULE

01	FIRST ISSUE	CAROL	2024.07.15
VER.	REVISED DESCRIPTION	REVISER	DATE