



J1 PIN ASSIGNMENT	
NO.	SYMBOL
1	FG
2	VSS
3	VDD
4	V0
5	/WR
6	/RD
7	/CE
8	C/D
9	NC
10	/RST
11	DB0
12	DB1
13	DB2
14	DB3
15	DB4
16	DB5
17	DB6
18	DB7
19	FS
20	VEE
21	LEDA
22	LEDK

J2 PIN ASSIGNMENT	
NO.	SYMBOL
1	VSS
2	VDD
3	V0
4	/WR
5	/RD
6	/CE
7	C/D
8	/RST
9	DB0
10	DB1
11	DB2
12	DB3
13	DB4
14	DB5
15	DB6
16	DB7
17	FS
18	VEE
19	LEDA
20	LEDK

- NOTES:
1. DISPLAY TYPE: FSTN, TRANSFLECTIVE, POSITIVE.
 2. DRIVE METHOD: 1/128 DUTY, 1/12 BIAS, VDD=5.0V, V0P=18.0V.
 3. VIEWING DIRECTION: 6:00 O'CLOCK.
 4. OPERATING TEMP.: -20°C ~ 70°C.
 5. STORAGE TEMP.: -30°C ~ 80°C.
 6. LED BACKLIGHT: WHITE LED.
 7. GENERAL TOLERANCE: ±0.3MM.
 8. ROHS COMPLIANT.

Mit MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL 2019.04.23	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI240128A-17
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		GRAPHIC MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
01	FIRST ISSUE	CAROL	2019.04.23