



CN1

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
FG	VSS	VDD	VO	WR	RD	CE	C/D	A	RST	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	FS	K

NOTES:

1. DISPLAY TYPE: FSTN, POSITIVE.
2. LCD TYPE: 1/64DUTY, 1/9BIAS, VOP=12V.
3. VIEWING DIRECTION: 6 O'CLOCK.
4. CONTROL IC: SAP1024B.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: YELLOW-GREEN LED, If=75mA, Vf=4.1V.
8. GENERAL TOLERANCE: ±0.3.
9. RoHS COMPLIANT.

03	CORRECT THE THICKNESS OF MODULE FROM 13.6mm(max.) to 14.5mm(max.)	RITA	2018.07.10
02	CORRECT ACTIVE AREA SIZE	CAROL	2015.05.08
01	FIRST ISSUE		2007.11.22
VER.	REVISED DESCRIPTION	REVISER	DATE

 MULTI-INNO TECHNOLOGY CO., LTD.			
DRAWN BY:	20071122	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI24064C-2
APPROVED BY:			DESCRIPTION:
VERSION NO:	03		GRAPHIC MODULE