


Pin	Symbol
1	N.C. (GND)
2	VSS
3	VCC
4	VCOMH
5	VLSS
6	D7
7	D6
8	D5
9	D4
10	D3
11	D2
12	D1
13	D0
14	E/RD#
15	R/W#
16	BS0
17	BS1
18	D/C#
19	CS#
20	RES#
21	FR
22	IREF
23	N.C.
24	VDDIO
25	VDD
26	VCI
27	VSL
28	VLSS
29	VCC
30	N.C. (GND)



- Notes:
1. Color: Light Blue
  2. Driver IC: SSD1322
  3. Die Size: 12374um x 1526um
  4. COF Number: SSD1322U
  5. Interface:  
8-bit 68XX/80XX Parallel, 3-/4-wire SPI
  6. General Tolerance: ±0.30
  7. The total thickness (2.10 Max) is without polarizer protective film & remove tape.  
The actual assembled total thickness with above materials should be 2.35 Max.

**Mit** MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2014.06.28	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	M125664D0-B
APPROVED BY:		DESCRIPTION:	OLED MODULE
VERSION NO:	01		

01	FIRST ISSUE	2014.06.28
VER.	REVISED DESCRIPTION	DATE