



DETAIL A
SCALE 20X

PIN DESCRIPTION

1	NC	16	BS0
2	VSS	17	BS1
3	VCC	18	DC#
4	VCOMH	19	CS#
5	VLSS	20	RES#
6	D7	21	FR
7	D6	22	IREF
8	D5	23	NC
9	D4	24	VDDIO
10	D3	25	VDD
11	D2	26	VCI
12	D1	27	VSL
13	D0	28	VLSS
14	E	29	VCC
15	R/W#	30	NC

NOTES:

1. OPERATING TEMP:-30°C TO 80°C
2. STORAGE TEMP: -40°C TO 85°C
3. VIEWING DIRECTION:ALL
4. OLED DRIVE IC:SSD1322
5. DISPLAY COLOR:RED
6. UNSPECIFIED TOLERANCES: ±0.2mm.
7. () MEANS: DIMENSION FOR REFERENCE
8. THE PROTECTIVE FILM ON FRONT SIDE OF OLED MUST BE REMOVED BEFORE ASSEMBLY BY CUSTOMER (客户在装机时, 自己必须撕掉保护膜)



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2016.03.28	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT:	MI25664FO-R
APPROVED BY:		mm	DESCRIPTION:
VERSION NO:	01		OLED MODULE

01	FIRST ISSUE	2016.03.28
VER.	REVISED DESCRIPTION	DATE