


FPC Pin Assignment

NO.	SYMBOL	NO.	SYMBOL
1	VSS(ESD)	16	R/W#
2	NC	17	E
3	VCC	18	D0
4	VCOMH	19	D1
5	VP	20	D2
6	NC	21	D3
7	VLSS	22	D4
8	VSS	23	D5
9	NC	24	D6
10	VDD	25	D7
11	VCI	26	BS1
12	VDDIO	27	BS2
13	CS#	28	IREF
14	RES#	29	NC
15	D/C#	30	VSS(ESD)



Dots Detail A
Scale 10X

NOTES:

- OPERATING TEMP: -30°C TO 80°C
- STORAGE TEMP: -40°C TO 85°C
- VIEWING DIRECTION: ALL
- OLED DRIVE IC: SSD1362Z
- DISPLAY COLOR: WHITE
- UNSPECIFIED TOLERANCES: ± 0.2 mm.
- () MEANS: DIMENSION FOR REFERENCE
- THE PROTECTIVE FILM ON FRONT SIDE OF OLED MUST BE REMOVED BEFORE ASSEMBLY BY CUSTOMER.



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2016.10.18	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI25664KO-W
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			OLED MOUDLE

01	FIRST ISSUE	2016.10.18
VER.	REVISED DESCRIPTION	DATE