


PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	VSS
3	VCC
4	VCOMH
5	VLSS
6	D7
7	D6
8	D5
9	D4
10	D3
11	D2
12	D1
13	DO
14	E/RD#
15	R/W#
16	BS0
17	BS1
18	DC#
19	CS#
20	RES#
21	FR
22	IREF
23	NC
24	VDDIO
25	VDD
26	VCI
27	VSL
28	VLSS
29	VCC
30	NC

NOTES:

- COLOR: GREEN
- OPERATING VOLTAGE: VCI=2.4V-3.5V
- DRIVE DUTY: 1/64
- DRIVER IC: SSD1322UR1
- OPERATING TEMP.: -40°C ~ 70°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 6800/8080 PARALLEL, 3-/4-WIRE SPI
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT

 MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	20220915		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI25664PO-G
APPROVED BY:			UNIT: mm	DESCRIPTION:
VER.	01	FIRST ISSUE	SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	RITA	2022.09.15
VER.	REVISED DESCRIPTION	REVISER	DATE