


PIN	NAME
1	NC
2	VLCD
3	VS+
4	VS-
5	VB0-
6	VB1-
7	VB1+
8	VB0+
9	VDD
10	VDD
11	VSS
12	VSS
13	NC
14	BMD
15	CS0
16	CD
17	WR1
18	WR0
19	RST
20	D0
21	D1
22	D2
23	D3
24	D4
25	D5
26	D6
27	D7
28	NC

NOTES:  
1. LED CIRCUIT DIAGRAM:  
LED: 1X7=7 dies



Cable Connector

PIN	NAME
1	A
2	K

- NOTES:
1. OPERATING TEMPERATURE: -20° C TO +70° C
  2. STORAGE TEMPERATURE: -30° C TO +80° C
  3. IC DRIVER: UC1698U
  4. LCD TYPE: FSTN, POSITIVE, TRANSFLECTIVE
  5. ROHS COMPLIANT (环保产品)
  6. BL: 7PCS WHITE LED If=70~140 mA VF: 2.8~3.4V
- TOLERANCE OF SEGMENTS TO EDGE OF GLASS ±0.2

CUSTOMER APVL .	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI320160A-G-2	
ENGR CHK	mm	MODEL	
APPROVAL		DWG NO	
MULTI-INNO TECHNOLOGY CO.,LTD.			PAGE 1/1