



Pin	Symbol
1	NC
2	VPP
3	VCOMH
4	VDD
5	IM1
6	IREF
7	CS
8	RES
9	DC
10	D0
11	D1
12	VSS
13	NC

NOTES:

1. DISPLAY TYPE: PASSIVE MATRIX OLED.
2. OPERATING VOLTAGE: VDD=2.8V.
3. VIEWING DIRECTION: FULL VIEWING ANGLE.
4. DRIVER IC: CH1115.
5. DISPLAY COLOR: WHITE.
6. OPERATING TEMP.: -40°C ~ 85°C.
7. STORAGE TEMP.: -40°C ~ 85°C.
8. INTERFACE: 4-WIRE SPI, I2C.
9. SURFACE LUMINANCE: 120CD/M²(TYP).
10. GENERAL TOLERANCE: ±0.3MM.
11. ROHS COMPLIANT.



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2020.07.17		MODULE P/N:
CHECKED BY:			SCALE : 1/1	M64128B10-W
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	CAROL	2020.07.17
VER.	REVISED DESCRIPTION	REVISER	DATE