



Scale (10:1)

PIN DESCRIPTION	
PIN	SYMBOL
1	NC
2	C2P
3	C2N
4	C1P
5	C1N
6	VBAT
7	VSS
8	VDD
9	BS1
10	BS2
11	CS#
12	RES#
13	D/C#
14	SCLK
15	SDIN
16	IREF
17	VCOMH
18	VCC
19	VLSS
20	NC

NOTES:

- COLOR: WHITE
- DRIVE DUTY: 1/48
- DRIVER IC: SSD1315
- OPERATING TEMP.: -40°C ~ 85°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 4-WIRE SPI
- ONLY THE SINGLE LAYER AREA ON FPC IS BENDABLE AND THE MINIMUM BEND RADIUS IS 1.5MM
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	CAROL	2020.04.28		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI6448DO-W1
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	OLED MODULE

VER.	REVISED DESCRIPTION	REVISER	DATE
01	FIRST ISSUE	CAROL	2020.04.28