



Pixel Detail
Scale (10:1)

PIN	SYMBOL	PIN DESCRIPTION
1	N.C.	(GND)
2	C2P	
3	C2N	
4	C1P	
5	C1N	
6	VBAT	
7	VSS	
8	VDD	
9	BS1	
10	BS2	
11	CS#	
12	RES#	
13	D/C#	
14	R/W#	
15	E/RD#	
16	D0	
17	D1	
18	D2	
19	D3	
20	D4	
21	D5	
22	D6	
23	D7	
24	IREF	
25	VCOMH	
26	VCC	
27	VLSS	
28	N.C.	(GND)

NOTES:

- COLOR: WHITE
- OPERATING VOLTAGE: VDD=3.3V (TYP.)
- DRIVE DUTY: 1/64
- DRIVER IC: SSD1315
- OPERATING TEMP.: -40°C ~ 85°C
- STORAGE TEMP.: -40°C ~ 85°C
- INTERFACE: 8-BIT 6800/8080 PARALLEL, 4-WIRE SPI, I²C
- GENERAL TOLERANCE: ±0.3MM
- ROHS COMPLIANT



MULTI-INNO TECHNOLOGY CO., LTD.

DRAWN BY:	RITA	2023.02.15		MODULE P/N:
CHECKED BY:			SCALE : 1/1	MI6448EQ-W
APPROVED BY:			UNIT: mm	DESCRIPTION:
VERSION NO:	01		SHEET NO.: 1/1	OLED MODULE

01	FIRST ISSUE	RITA	2023.02.15
VER.	REVISED DESCRIPTION	REVISER	DATE